

InnoVet[®] Specialist

HIGH FREQUENCY RADIOGRAPHIC SYSTEM



The
Specialist's
Choice

"THE MOST TRUSTED NAME IN VETERINARY RADIOGRAPHY"

Designed by veterinarians for veterinarians, The InnoVet Specialist is designed to meet the needs of busy animal hospitals and specialty practices.

INNOVET MEANS INTEGRITY

InnoVet revolutionized veterinary radiography in 1991 with the first x-ray system designed by veterinarians. Since then, InnoVet has manufactured more than 15,000 veterinary x-ray systems, making it the #1 veterinary x-ray manufacturer in the United States.

Add to that, the industry's best warranty and it's no wonder InnoVet is the most trusted name in veterinary radiography.



Optional extended rails and wall cassette holder shown above

LOCAL SUPPORT

Capital equipment is a long-term investment that deserves personal attention from a service professional who understands your practice.

Regional InnoVet dealers are factory-trained to install and service your x-ray systems with immediate on-site and remote support. Our trusted support network means image quality will never slow down your practice.

INDUSTRY BEST WARRANTY

Our 7-Year limited parts warranty secures your investment today and guarantees your investment value tomorrow.

DIGITAL READY - RIGHT FOR TODAY OR TOMORROW

Our systems are compatible with most digital imaging systems.

InnoVet®

7555 N. Caldwell Ave. • Niles, IL 60714

800-972-9776 • 773-588-2444

www.innovet4vets.com

SYSTEM SPECIFICATION

HIGH FREQUENCY GENERATOR

- 20 kHz High Frequency technology
- 30 kW power rating
- kVp range: 40 – 125, 1 kV increments
- mAs range: 0.5 to 400 with over 100 mAs selections
- mAs/kVp technique selection
- Digital mAs, mA and kVp readout
- UL Classified

TABLE

- Table top: 76 in. x 30 in.
- Welded base construction supports 400 lb. animal
- Effortless table top travel
- Grid cabinet with electric lock
- Heavy duty tray
- Angulation dial and deluxe operator handgrips

TUBESTAND

- Floor-to-wall or ceiling tubestand with 5 ft. rails
- Full range of vertical travel
- Electric locks
- Angulation dial and operator handgrips

X-RAY TUBE

- 1.0-2.0 mm F.S., 140,000 H.U. with 90° horns

CABLES

- 15 ft. high voltage cables with federal terminations

COLLIMATOR

- Manual collimator with light field and swivel mount
- Field light "on" time - selectable 30, 45 or 60 seconds

SYSTEM OPTIONS

- 40 kW high frequency generator upgrade
- Anatomical programming upgrade
- 500 mA generator upgrade
- Upgrade to variable height elevator table
- Extended tubestand rails for off-table exams
- Wall cassette holder